



RZ400 10W40 Engine Oil

RZ400 10W40 is a high-quality engine oil based on HC synthesis for passenger cars and light commercial vehicles with excellent protection against wear, corrosion, oil oxidation, piston deposits and sludge. It offers superior temperature stability and oxidation resistance. It is used in modern multi-cylinder, multi-valve, suction, compressor and turbo engines.

Compatibility:

- ACEA A3 / B4
- API SL / CF
- MB 229.1
- VW 501 01 / 505 00
- Fiat 9.55535-G2 / D2

Advantages:

- Eminently suitable for turbocharged engines
- Prevention of adhesion, lacquering and coking of cylinders, pistons, valves and turbochargers in a reliable manner
- Safer year-round operation due to outstanding viscosity-temperature behaviour and high shear stability
- Stable lubricating film, even with hot oil and under excessive loads
- Very low oil consumption
- High level of oxidation protection by means of selected HC synthetic oils and special additives
- Reliable protection against 'black sludge'
- Proper functioning of hydraulic tappets (hydraulic valve clearance compensation)



Our synthetic motor oil RZ400 provides excellent protection against wear and oxidation in cars, light and heavy trucks. It also offers unmatched temperature stability to get the best performance for the engine in harsh conditions.

Content: 4,0 Liter

Content Carton: 4 cans

Content: 60,0 Liter

Content Sea pallet: 9 drums

Content: 200,0 Liter

Content Sea pallet: 4 drums

Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0,862
Kinematic viscosity KV 40	ASTM D-7042	mm ² /s	93,0
Kinematic viscosity KV 100	ASTM D-7042	mm ² /s	14,2
Viscosity index	ASTM D-7042	-	160
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	190
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-33
CCS	ASTM D-5293	cP @ °C	5300 @ -25
Total base number	DIN 51639-1	mgKOH/g	10,3
Acid number	-	mgKOH/g	< 1
HTHS	ASTM D4683	mPas	4,1

These parameters are typical of current production. The data does not include any assurance of properties or the guarantee of suitability for a special application. Existing statutory provisions and ordinances, which relate to the handling and use of the products, must be observed by the recipient of our products.