



RZ400 5W30 Engine Oil

RZ400 5W30 has an advanced formula that lubricates, cleans and protects engines. It is designed to provide an excellent level of protection against wear, deposit formation and superior performance under the most demanding conditions. It has great fluidity at low temperature and viscosity stability at high temperature. It can also reduce oil consumption and emissions.

Compatibility:

- API SP
- ILSAC GF-6
- dexos 1 Gen. 2
- Ford WSS-M2C961-A1
- Ford WSS-M2C946-A

Advantages:

- Low-speed pre-ignition prevention
- Small deposits and wear
- Better properties than API SM referring resistance to aging
- Stability of viscosity
- Fuel saving
- Low exhaust gas emission
- Engine cleanliness
- Piston cleanliness
- Flexible maintenance intervals

Our synthetic motor oil RZ400 provides excellent protection against wear and oxidation in cars, light and heavy trucks. It also offers unmatched temperature stability to get the best performance for the engine in harsh conditions.

Content: 4,0 Liter

Content Carton: 4 cans

Content: 60,0 Liter

Content Sea pallet: 9 drums

Content: 200,0 Liter

Content Sea pallet: 4 drums

Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	DIN EN ISO 12185	g/ml	0,840 – 0,860
Kinematic viscosity KV 100	DIN 51562-1	mm ² /s	10,2 – 11,9
Viscosity index	DIN ISO 2909	-	min. 165
Flash point	DIN EN ISO 2592	°C	min. 200
Pour point	DIN EN ISO 3016	°C	max. -36
Total base number	DIN ISO 3771	mgKOH/g	7,8 – 9,4

These parameters are typical of current production. The data does not include any assurance of properties or the guarantee of suitability for a special application. Existing statutory provisions and ordinances, which relate to the handling and use of the products, must be observed by the recipient of our products.

RZ Oil by CP Power Solutions GmbH | Weidenweg 12 | D-73087 Bad Boll

info@rz-international.com

www.rz-international.com

