



RZ50E Engine Protector

RZ50E Engine Protector is specially developed as a high-performance motor oil treatment to reduce friction and wear and condition metal surfaces.

- Fights metal to metal friction by providing a thicker cushion between moving engine parts.
- Improves compression and the viscosity index of the oil and prevents premature thickening of new oil.
- Superior engine performance and wear protection.
- Helps to maximize protection levels and performance.
- Compatible with all mineral, synthetic oils and suitable for regular and low SAPS applications.
- For petrol, diesel, LPG and hybrid engines (with or without turbocharger).

Application:

- For all gasoline and diesel engine lubrication system.

Usage direction:

One can (300 ml) is designed for 5 liters of engine oil. Add the contents of the can to the oil circuit. The additive remains in the engine oil until the next oil change.

Our high-performance additives for gasoline and diesel engines ensure noticeable improvements in the properties of the engine in fuel or in engine oil.

Content: 300 ml

Content Carton: 24 cans

Typical characteristics

Property	Method	Unit	Value
Colour		-	Maroon
Odor		-	Characteristic odour
Physical state		-	Oily
Kinematic viscosity	ISO 3104/3105	g/ml	14,54
Boiling point and boiling range		°C	190
Flash point	DIN EN ISO 2592	°C	220
Autoflammability		°C	230
Relative density		g/ml	0,89
Water solubility		-	Insoluble

These parameters are typical of current production. The data does not include any assurance of properties or the guarantee of suitability for a special application. Existing statutory provisions and ordinances, which relate to the handling and use of the products, must be observed by the recipient of our products.

RZ Oil by CP Power Solutions GmbH | Weidenweg 12 | D-73087 Bad Boll

info@rz-international.com

www.rz-international.com

