



RZ5E Viscosity Improver

RZ5E Viscosity Improver is developed to restore the viscosity of the engine oil.

- Known as Oil Booster to protect the engine oil against premature deterioration.
- Helps to prevent oil from breaking down, counteract oil thinning by boosting viscosity and increasing the anti-wear property.
- Improves compression and the viscosity index of the oil and prevents metal-to-metal friction.
- Compatible with all mineral, synthetic oils and suitable for regular and low SAPS applications.
- For petrol, diesel, LPG and hybrid engines (with or without turbocharger).

Application:

- For all gasoline and diesel engine lubrication system.

Usage direction:

One can (300 ml) is designed for 5 liters of engine oil. Add the contents of the can to the oil circuit. The additive remains in the engine oil until the next oil change.

Our high-performance additives for gasoline and diesel engines ensure noticeable improvements in the properties of the engine in fuel or in engine oil.

Content: 300 ml

Content Carton: 24 cans



Typical characteristics

Property	Method	Unit	Value
Colour		-	Yellow-Gold
Odor		-	Characteristic odour
Physical state		-	Oil
Kinematic viscosity	ISO 3104/3105	g/ml	664,66
Boiling point and boiling range		°C	180-250
Flash point	DIN EN ISO 2592	°C	234
Relative density		g/ml	0,88
Water solubility		-	Insoluble

These parameters are typical of current production. The data does not include any assurance of properties or the guarantee of suitability for a special application. Existing statutory provisions and ordinances, which relate to the handling and use of the products, must be observed by the recipient of our products.