



RZ59E Ceramic Engine Protector

RZ59E Ceramic Engine Protector is a high-performance engine oil additive that provides engine with the utmost level of protection; with a superior performance even under the extreme conditions.

- High-tech ceramic wear protection that prevents direct metal-on-metal friction with excellent heat dissipation.
- With lubricating film on the most critical and wear-sensitive parts of the engine.
- Improves efficiency, horse power/torque and top speed.
- Provides maximum protection level and performance.
- Suitable for turbo/supercharged engines and high-performance engines.

Application:

• For all gasoline and diesel engine lubrication system.

Usage direction:

One can (300 ml) is designed for 5 liters of engine oil. Add the contents of the can to the oil circuit. The additive remains in the engine oil until the next oil change.



Our high-performance additives for gasoline and diesel engines ensure noticeable improvements in the properties of the engine in fuel or in engine oil.

Content: 300 ml
Content Carton: 24 cans

Typical characteristics

Typical characteristics			
Property	Method	Unit	Value
Colour		-	White
Odor		-	Characteristic odour
Physical state		-	Oil
Kinematic viscosity	ISO 3104/ <mark>3105</mark>	g/ml	90
Boiling point and boiling range		°C	190
Flash point	DIN EN ISO 2592	°C	220
Relative density		g/ml	0,9
Water solubility		-	Insoluble

These parameters are typical of current production. The data does not include any assurance of properties or the guarantee of suitability for a special application. Existing statutory provisions and ordinances, which relate to the handling and use of the products, must be observed by the recipient of our products.