



RZ70E Oil Stop Leak

RZ70E Oil Stop Leak is specifically formulated to control engine oil leaks due to deteriorated or worn seals and gaskets including the rear main seal.

- Strong and fast sealing performance, stops leaks fast.
- Rejuvenates all rubber seals & gaskets in engines.
- Restores the elasticity of rubber, neoprene oil seal rings and O-rings.
- Does not influence oil quality or viscosity.
- Compatible with petroleum and all mineral, synthetic oils and low SAPS applications.
- For all petrol and diesel engines and engines with or without turbocharger and with stationary equipment.

Application:

- For all gasoline and diesel engine lubrication system.

Usage direction:

One can (300 ml) is designed for 5 liters of engine oil. Add the contents of the can to the oil circuit. The additive remains in the engine oil until the next oil change.

Our high-performance additives for gasoline and diesel engines ensure noticeable improvements in the properties of the engine in fuel or in engine oil.

Content: 300 ml

Content Carton: 24 cans cans

Typical characteristics

Property	Method	Unit	Value
Colour		-	Yellow-Gold
Odor		-	Characteristic odour
Physical state		-	Oil
Kinematic viscosity	ISO 3104/3105	g/ml	3500
Boiling point and boiling range		°C	180-250
Flash point	DIN EN ISO 2592	°C	210
Relative density		g/ml	0,88
Water solubility		-	Insoluble

These parameters are typical of current production. The data does not include any assurance of properties or the guarantee of suitability for a special application. Existing statutory provisions and ordinances, which relate to the handling and use of the products, must be observed by the recipient of our products.

RZ Oil by CP Power Solutions GmbH | Weidenweg 12 | D-73087 Bad Boll

info@rz-international.com

www.rz-international.com

