



## RZ 200 GT 5W50 Engine Oil

RZ-GT 5W50 is designed for high stress racing environment and perfect for touring and sport bikes. Extraordinary additive package offers increased anti-foaming qualities and a higher viscosity index of stability at a broader range of extreme temperatures. Unsurpassed wear protection and friction reduction provide ultimate performance and racing acceleration for racing motors.

### Compatibility:

- API SN
- JASO MA / MA2

### Application:

- Suitable for four-stroke racing motorcycle or scooter engines with wet or dry clutch system.

### Advantages:

- Exceptional wear protection
- Excellent shear stability
- Optimized friction properties
- Outstanding low-temperature behavior
- Excellent detergent / dispersant behavior
- Also suitable for wet clutches
- Effective rust and corrosion protection
- For maximum motor protection

RZ200 Motor Oil is suitable for all kinds of two / four-Stroke, sport motorcycle or scooter engine, with unsurpassed lubricating performance and wear protection to provide ultimate performance and racing acceleration for racing motors.

**Content:** 1,0 Liter

**Content Carton:** 10 cans

**Content:** 60,0 Liter

**Content Sea pallet:** 9 drums

**Content:** 200,0 Liter

**Content Sea pallet:** 4 drums



### Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	DIN 51 757	g/ml	0,855
Kinematic viscosity KV 40	DIN 51 562	mm <sup>2</sup> /s	110
Kinematic viscosity KV 100	DIN 51 562	mm <sup>2</sup> /s	18,5
Viscosity index	DIN ISO 2909	-	190
Flash point	DIN EN ISO 2592	°C	235
Pour point	DIN EN ISO 3016	°C	-42
Total base number	DIN ISO 3771	mgKOH/g	7,0

These parameters are typical of current production. The data does not include any assurance of properties or the guarantee of suitability for a special application. Existing statutory provisions and ordinances, which relate to the handling and use of the products, must be observed by the recipient of our products.