



RZ 200 TSZ-4T 10W40 Engine Oil

RZTSZ-4T 10W40 is fully synthetic oil for 4-stroke motorcycle engines with a motorcycle-specific additive pack. It's designed to protect engines at high RPM and temperatures. It keeps the clutch safe and provides maximum power transfer. Its advanced cleaning capabilities and shear stability help the engine to perform the best.

Compatibility:

- API SL/SJ/SH/SG
- JASO MA2

Application:

- Suitable for four-stroke motorcycle or scooter engines with wet or dry clutch system.

Advantages:

- Excellent wear protection
- Virtually residue-free combustion
- 'Low smoke' formulation
- Reduced deposits on piston rings, outlet ports and spark plugs
- Prevention of glow ignition in a reliable manner
- Multi-functional application possibilities
- Suitable for air-cooled and water-cooled 2-stroke engines
- Suitable for both separate and mixed lubrication

RZ200 Motor Oil is suitable for all kinds of two / four-Stroke, sport motorcycle or scooter engine, with unsurpassed lubricating performance and wear protection to provide ultimate performance and racing acceleration for racing motors.

Content: 1,0 Liter

Content Carton: 10 cans

Content: 60,0 Liter

Content Sea pallet: 9 drums

Content: 200,0 Liter

Content Sea pallet: 4 drums



Typical characteristics

| Property | Method | Unit | Value |
|----------------------------|-----------------------------|--------------------|-------|
| Density at 15 °C | ASTM D-7042 | g/ml | 0,863 |
| Kinematic viscosity KV 40 | ASTM D-7042 | mm ² /s | 96,0 |
| Kinematic viscosity KV 100 | ASTM D-7042 | mm ² /s | 14,3 |
| Viscosity index | ASTM D-7042 | - | 154 |
| Flash point | ASTM D-92 / DIN EN ISO 2592 | °C | 244 |
| Pour point | ASTM D-97 / DIN EN ISO 3016 | °C | -29 |
| Total base number | DIN 51639-1 | mgKOH/g | 7,6 |

These parameters are typical of current production. The data does not include any assurance of properties or the guarantee of suitability for a special application. Existing statutory provisions and ordinances, which relate to the handling and use of the products, must be observed by the recipient of our products.