

RZ 200 TSZ-4T 5W40 Engine Oil

RZTSZ-4T 5W40 is fully synthetic oil for 4-stroke motorcycle engines with a motorcyclespecific additive pack. It's designed to protect engines at high RPM and temperature. It keeps the clutch safe and provides maximum power transfer. Its advanced cleaning capabilities and shear stability help the engine to perform the best.

Compatibility:


- API SL/SJ/SH/SG
- JASO MA2

Application:

Suitable for four-stroke motorcycle or scooter engines with wet or dry clutch

Advantages:

- Outstanding protection against wear and corrosion of the engine and gears
- Stable lubricating film, even with very hot oil and under very high loads
- Extremely stable to shear stress 'Stay-in-grade'
- Excellent clutch performance; meets the stringent JASO MA2 requirements
- The favourable cold viscosity ensures rapid lubrication and low 'cold wear'
- High level of oxidation protection by means of selected HC synthetic oils and special additives



Content: 1,0 Liter Content Carton: 10 cans Content: 60.0 Liter

Content: 200.0 Liter

Content Sea pallet: 9 drums

Content Sea pallet: 4 drums

Typical characteristics

Typical characteristics			
Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0,864
Kinematic viscosity KV 40	ASTM D-7042	mm²/s	86,0
Kinematic viscosity KV 100	ASTM D-7042	mm²/s	14,3
Viscosity index	ASTM D-7 <mark>042</mark>	-	173
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	228
Pour point	ASTM D-9 <mark>7 / DIN EN ISO 3016</mark>	°C	-35

These parameters are typical of current production. The data does not include any assurance of properties or the guarantee of suitability for a special application. Existing statutory provisions and ordinances, which relate to the handling and use of the products, must be observed by the recipient of our products.

