



RZ600 0W20 Engine Oil

RZ600 0W20 100% Synthetic Motor Oil is engineered with low viscosity and low friction, suitable for all seasons. It has superior temperature stability, oxidation resistance, fast cold starting property and excellent wear and corrosion protection. Its high detergency keeps the engine optimally clean.

Compatibility:

- API SP
- ILSAC GF-6A

Advantages:

- Low-speed pre-ignition (LSPI) prevention
- Small deposits and wear
- Fuel saving
- Low exhaust gas emission engine cleanliness
- Piston cleanliness
- Flexible maintenance intervals



RZ600 100% Synthetic Motor Oil is suitable for gasoline and diesel engines such as home or commercial cars and coaches, meeting the requirements of engine to the latest emission standards.

Content: 1,0 Liter
Content Carton: 10 cans
Content: 60,0 Liter
Content Sea pallet: 9 drums

Content: 4,0 Liter
Content Carton: 4 cans
Content: 200,0 Liter
Content Sea pallet: 4 drums

Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	DIN EN ISO 12185	g/ml	0,840 – 0,860
Kinematic viscosity KV 100	DIN 51562-1	mm ² /s	7,8 – 9,3
Viscosity index	DIN ISO 2909	-	Min. 165
Flash point	DIN EN ISO 2592	°C	Min. 200
Pour point	DIN EN ISO 3016	°C	Max. -36
CCS	DIN 51377	cP @ °C	Max. 6200 @ -35
Total base number	DIN ISO 3771	mgKOH/g	7,8 – 9,4

These parameters are typical of current production. The data does not include any assurance of properties or the guarantee of suitability for a special application. Existing statutory provisions and ordinances, which relate to the handling and use of the products, must be observed by the recipient of our products.