



## RZ600 + 5W30 Engine Oil

RZ600+ 5W30 has been developed to be used as universal lubricant in all the gasoline and diesel (without Diesel Particulate Filter) engine. Specifically designed to help prevent LSPI and focus on turbocharger-specific standards for GF-6. It delivers unsurpassed levels of protection across a variety of driving conditions and temperatures. Prevent permanent damage to cylinder walls, pistons, piston rings, connecting rods and spark plugs.

### Compatibility

- API SP RC
- ILSAC GF-6A
- GM dexos 1 Gen 2
- Ford WSS-M2C929-A / 946-A
- Chrysler MS-6395 (T)
- Ford WSS-M2C945-A
- GM 6094M / 4718M
- Honda / Acura HTO-06

### Advantages:

- The excellent resistance during operation with ethanol (E85) protects against corrosion and white sludge
- Improved piston, turbocharger and engine cleanliness
- For reliable operation, maximum mileage and lower service costs
- Very good cold-starting properties and rapid engine lubrication
- Low oil consumption due to a very low evaporation loss
- Highest oxidation stability due to special HC synthetic oils

RZ600 100% Synthetic Motor Oil is suitable for gasoline and diesel engines such as home or commercial cars and coaches, meeting the requirements of engine to the latest emission standards.

**Content:** 1,0 Liter

**Content Carton:** 10 cans

**Content:** 60,0 Liter

**Content Sea pallet:** 9 drums

**Content:** 200,0 Liter

**Content Sea pallet:** 4 drums



### Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0,849
Kinematic viscosity KV 40	ASTM D-7042	mm <sup>2</sup> /s	60,12
Kinematic viscosity KV 100	ASTM D-7042	mm <sup>2</sup> /s	10,8
Viscosity index	ASTM D-7042	-	173
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	235
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-39
CCS	ASTM D-5293	cP @ °C	4500 @ -30
Total base number	DIN 51639-1	mgKOH/g	9,0
HTHS	ASTM D4683	mPas	3,1

These parameters are typical of current production. The data does not include any assurance of properties or the guarantee of suitability for a special application. Existing statutory provisions and ordinances, which relate to the handling and use of the products, must be observed by the recipient of our products.