



RZ600 5W40 Engine Oil

RZ600 5W40 100% Synthetic Motor Oil improves engine performance and power. It provides a lubricating film at the cold start in an extremely quick and stable way and offers high thermal stability under heavy-duty operating conditions. It has excellent wear protection and friction reduction. Its high detergency keeps the engine optimally clean.

Compatibility:

- ACEA A3 / B4
- API SN / CF
- MB 229.3 / 226.5
- VW 502 00/505 00
- Porsche A40
- GM-LL-B-025
- Renault RN 0700/071
- PSA B71 2296

Advantages:

- Eminently suitable for turbocharged engines
- Prevention of adhesion, lacquering and coking of cylinders, pistons, valves and turbochargers in a reliable manner
- Safer year-round operation due to outstanding viscosity-temperature behaviour and high shear stability
- Good cold-starting properties and rapid engine lubrication
- Stable lubricating film, even with hot oil and under excessive loads
- High level of oxidation protection by means of selected HC synthetic oils and special additives

RZ600 100% Synthetic Motor Oil is suitable for gasoline and diesel engines such as home or commercial cars and coaches, meeting the requirements of engine to the latest emission standards.

Content: 1,0 Liter
Content Carton: 10 cans
Content: 60,0 Liter
Content Sea pallet: 9 drums

Content: 4,0 Liter
Content Carton: 4 cans
Content: 200,0 Liter
Content Sea pallet: 4 drums



Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0,85
Kinematic viscosity KV 40	ASTM D-7042	mm ² /s	86,0
Kinematic viscosity KV 100	ASTM D-7042	mm ² /s	14,2
Viscosity index	ASTM D-7042	-	174
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	236
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-36
CCS	ASTM D-5293	cP @ °C	6100 @ -30
Total base number	DIN 51639-1	mgKOH/g	10,1
HTHS	ASTM D4683	mPas	4,0

These parameters are typical of current production. The data does not include any assurance of properties or the guarantee of suitability for a special application. Existing statutory provisions and ordinances, which relate to the handling and use of the products, must be observed by the recipient of our products.