

RZ600 5W50 Engine Oil

RZ600 5W50 100% Synthetic Motor Oil improves engine performance and power. It provides a lubricating film at the cold start in an extremely quick and stable way and offers high thermal stability under heavy-duty operating conditions. It has excellent wear protection and friction reduction. Its high detergency keeps the engine optimally clean. Due to the very low evaporation loss, the oil consumption is also very low.

Compatibility:

- ACEA A3 / B4 •
- API SN / CF
- MB 229.3
- VW 502 00/505 00
- **BMW Longlife-98**

Advantages:

- Excellent for turbo engines ٠
- Reliably prevents sticking, varnishing and coking of cylinders, pistons, valves and turbochargers
- Safe year-round operation thanks to excellent viscosity-temperature behavior • and high shear stability
- Good cold start properties and quick engine lubrication .
- Stable lubricating film even with hot oil and extreme loads
- Reliable protection against "black sludge"
- Flawless operation of hydraulic tappets (hydraulic valve lash compensation)
- Low oil consumption due to very low evaporation loss
- Miscible and compatible with conventional and synthetic brand motor oils.

RZ600 100% Synthetic Motor Oil is suitable for gasoline and diesel engines such as home or commercial cars and coaches, meeting the requirements of engine to the latest emission standards.

Content: 1,0 Liter Content Carton: 10 cans Content: 60,0 Liter Content Sea pallet: 9 drums Content: 4,0 Liter Content Carton: 4 cans Content: 200,0 Liter Content Sea pallet: 4 drums

Typical characteristics

Typical characteristics			
Property	Method	Unit	Value
Density at 15 °C	ASTM D-7 <mark>042</mark>	g/ml	0,853
Kinematic viscosity KV 40	ASTM D-7042	mm²/s	112
Kinematic viscosity KV 100	ASTM D-7042	mm²/s	18,5
Viscosity index	ASTM D-7042	-	185
Flash point	ASTM D-92 / DIN EN ISO <mark>2592</mark>	°C	>200
Pour point	ASTM D-97 / DIN EN ISO <mark>3016</mark>	°C	-33
HTHS	ASTM D4683	mPas	4,8


These parameters are typical of current production. The data does not include any assurance of properties or the guarantee of suitability for a special application. Existing statutory provisions and ordinances, which relate to the handling and use of the products, must be observed by the recipient of our products.

RZ Oil by CP Power Solutions GmbH | Weidenweg 12 | D-73087 Bad Boll

info@rz-international.com

www.rz-international.com





1 Liter Θ Made in EU, Germany DIN EN ISO 9001:2015 CERT DIN EN ISO 14001:2015