



RZ800 5W20 EC Engine Oil

RZ800 5W20 EC is high-performance energy-conservative fully synthetic motor oil for modern generation car engines. It helps to keep the engine clean by minimizing deposit formation. Its excellent sludge and deposit control enable the engine to serve long. It has superior temperature stability and oxidation-resistance as well as fast cold starting property and excellent anti-wear property. It provides consistent rust protection caused by harmful acids generated by engine contaminations.

Compatibility:

- ACEA A1 / B1
- Jaguar Land Rover STJLR.03.5004
- Ford WSS-M2C925-A/ -B

Advantages:

- Best fuel economy performance
- Low oil consumption and low evaporation loss
- Very good cold-starting properties and rapid engine lubrication
- Stable lubricating film, even with hot oil and under excessive loads
- High level of oxidation protection by means of selected HC synthetic oils and special additives

RZ800 100% Synthetic Motor Oil is especially suitable for use in gasoline and diesel engines of mid/high-end home or commercial cars and passenger cars. Blended with high-quality PAO fully synthetic base oil and additive technology.

Content: 1,0 Liter Content Carton: 10 cans Content: 60,0 Liter Content Sea pallet: 9 drums

Content: 200,0 Liter Content Sea pallet: 4 drums

Typical characteristics

Property	Method	Unit	Value
D <mark>ensity at 15 °C</mark>	ASTM D-7042	g/ml	0,851
Kinematic viscosity KV 40	ASTM D-7042	mm²/s	48,5
Kinematic viscosity KV 100	ASTM D-7042	mm²/s	8,5
Viscosity index	ASTM D-7042	-	154
Flash point	ASTM D-9 <mark>2 / DIN EN ISO 2592</mark>	°C	232
Pour point	ASTM D-9 <mark>7 / DIN EN ISO 3016</mark>	°C	-38
CCS	ASTM D-5293	cP @ °C	<mark>5350 @ -</mark> 30
Total base number	DIN 51639-1	mgKOH/g	8,9
нтнѕ	ASTM D4683	mPas	2,83



These parameters are typical of current production. The data does not include any assurance of properties or the guarantee of suitability for a special application. Existing statutory provisions and ordinances, which relate to the handling and use of the products, must be observed by the recipient of our products.

RZ Oil by CP Power Solutions GmbH | Weidenweg 12 | D-73087 Bad Boll info@rz-international.com

