



RZ800 5W40 Engine Oil

RZ800 5W40 high-performance fully synthetic motor oil is formulated for ultimate engine performance and protection under all operating conditions. It provides better fuel economy, reduces emission and prolongs engine lives with excellent wear protection and friction reduction. It is used in gasoline, LPG and diesel engines of passenger cars and light-duty commercial vehicles equipped with soot filters.

Compatibility:

- API SN/CF
- ACEA C3
- MB 229.51 / 229.31 / 226.5
- VW 502 00 / 505 00 / 505 01
- Porsche A40
- Renault RN0700 / 0710
- Ford WSS-M2C917-A
- Fiat 9.55535-S2 / T2
- dexos 2

Recommended:

- BMW Longlife-04

Advantages:

- It meets the requirements of the VW 'Pumpe-Düse' (unit injector or 'PD') VW 505 01 specification
- The low sulphated ash, low phosphorus and Sulphur content protects diesel particulate filters and catalytic converters
- Hinders the formation of deposits in the engine. As a result, it guarantees first-rate operational safety performance and low maintenance costs.
- Low oil consumption due to a very low evaporation loss
- Good cold-starting properties and rapid engine lubrication

RZ800 100% Synthetic Motor Oil is especially suitable for use in gasoline and diesel engines of mid/high-end home or commercial cars and passenger cars. Blended with high-quality PAO fully synthetic base oil and additive technology.

Content: 1,0 Liter
Content Carton: 10 cans
Content: 60,0 Liter
Content Sea pallet: 9 drums

Content: 4,0 Liter
Content Carton: 4 cans
Content: 200,0 Liter
Content Sea pallet: 4 drums

Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0,848
Kinematic viscosity KV 40	ASTM D-7042	mm ² /s	86,9
Kinematic viscosity KV 100	ASTM D-7042	mm ² /s	14,3
Viscosity index	ASTM D-7042	-	170
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	236
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-36
CCS	ASTM D-5293	cP @ °C	6250 @ -30
Total base number	DIN 51639-1	mgKOH/g	7,8

These parameters are typical of current production. The data does not include any assurance of properties or the guarantee of suitability for a special application. Existing statutory provisions and ordinances, which relate to the handling and use of the products, must be observed by the recipient of our products.

