



## RZ800 5W50 Engine Oil

RZ800 5W50 is an advanced fully synthetic motor oil with PAO base specifically developed to be used as universal lubricant in all the gasoline and diesel engines, including the new EURO IV engines with after treatment devices like DPF, CAT and the latest generation injection. It protects emission systems by helping to keep diesel particulate filters clean. It has excellent fuel economy and effectively reduces harmful emissions. It delivers unsurpassed levels of protection across a variety of driving conditions and temperatures.

### Compatibility:

- ACEA C3
- API SN/CF
- BMW Longlife-04
- Fiat 9.55535-S2/T2
- Ford WSS-M2C917-A
- GM dexos2
- MB 229.31/229.51/226.5
- Porsche A40
- Renault RN 0700/0710
- VW 502 00/505 00/505 01

### Advantages:

- The low sulphated ash, low phosphorus and Sulphur content protects diesel particulate filters and catalytic converters
- Hinders the formation of deposits in the engine. As a result, it guarantees first-rate operational safety performance and low maintenance costs.
- Low oil consumption due to a very low evaporation loss
- Good cold-starting properties and rapid engine lubrication

RZ800 100% Synthetic Motor Oil is especially suitable for use in gasoline and diesel engines of mid/high-end home or commercial cars and passenger cars. Blended with high-quality PAO fully synthetic base oil and additive technology.

**Content:** 1,0 Liter  
**Content Carton:** 10 cans  
**Content:** 60,0 Liter  
**Content Sea pallet:** 9 drums

**Content:** 4,0 Liter  
**Content Carton:** 4 cans  
**Content:** 200,0 Liter  
**Content Sea pallet:** 4 drums



### Typical characteristics

Property	Method	Unit	Value
Density at 15 °C	ASTM D-7042	g/ml	0,867
Kinematic viscosity KV 40	ASTM D-7042	mm <sup>2</sup> /s	114
Kinematic viscosity KV 100	ASTM D-7042	mm <sup>2</sup> /s	18,5
Viscosity index	ASTM D-7042	-	181
Flash point	ASTM D-92 / DIN EN ISO 2592	°C	230
Pour point	ASTM D-97 / DIN EN ISO 3016	°C	-30
CCS	ASTM D-5293	cP @ °C	6000 @ -30
Total base number	DIN 51639-1	mgKOH/g	7,1
HTHS	ASTM D4683	mPas	4,0

These parameters are typical of current production. The data does not include any assurance of properties or the guarantee of suitability for a special application. Existing statutory provisions and ordinances, which relate to the handling and use of the products, must be observed by the recipient of our products.